

**PLC:**

- CPU222, Power Supply 110/220 VAC, 8DI 24Vdc / 6DO Relay 2A, Memory 4KB, 1 MPI/PPI Port, Max. 2 Expansion Modules.
- CPU224, Power Supply 24 Vdc, 14DI 24Vdc / 10DO 24Vdc, Memory 8KB, 1 MPI/PPI Port, Max. 7 Expansion Modules.
- CPU224, Power Supply 110/220 VAC, 14DI 24Vdc / 10DO Relay, Memory 8/12KB, 1 MPI/PPI Port, Max. 7 Expansion Modules.
- CPU224XP, Power Supply 24Vdc, 14DI 24Vdc / 10DO 24Vdc, 2 Analog Inputs 0–10Vdc, 1 Analog Output V/I, 2 MPI/PPI Ports, Max. 7 Expansion Modules.
- CPU224XP, Power Supply 120/220 VAC, 14DI 24Vdc / 10DO Relay 2A, 2 Analog Inputs 0–10Vdc, 1 Analog Output V/I, 2 MPI/PPI Ports, Max. Expansion Modules.
- CPU226, Power Supply 24 Vdc, 24DI 24Vdc / 16DO 24Vdc, Memory 16/24KB, 2 MPI/PPI Ports, Max. 7 Expansion Modules.
- CPU226, Power Supply 110/220 VAC, 24DI 24Vdc / 16DO Relay 2A, Memory 16/24KB, 2 MPI/PPI Ports, Max. 7 Expansion Modules.

Digital Input Modules**Digital Output Modules****Digital Input/Output Modules.****Specialized Modules such as:**

- Weighing module for CPUs 222/224/226 SIWAREX-MS.
- EM231 Module with 4 analog inputs +/-10Vdc, 12-bit resolution, only for CPU S7-22X.
- EM231 Module with 4 analog inputs for thermocouples types J, K, S, T, R, E, N, 12-bit resolution. Only for CPU S7-22X.
- EM231 Module with 2 analog inputs for RTD PT100/200/500/1000/10000. Only for CPU S7-22X.
- EM232 Module with 2 analog outputs +/-10Vdc, 12-bit resolution. Only for CPU S7-22X.
- EM235 Module with 4 inputs, 1 analog output, 12-bit resolution, only for CPU S7-22X.
- EM277 PROFIBUS Slave DP/MPI communication interface.
- CP243-2 AS-Interface V2.1 Master, up to 62 slaves.
- CP243-1 Industrial Ethernet interface, 10/100 Mbit/s, TCP/IP OPC for CPU 22X.

